

Data sheet:

## Com-Server++



Article no.: 58665

**EUR 318.00**

\*Net price for commercial users

### One serial port to the network - transparent, fast, universal

The Com-Server++ integrates a serial device into the network via TCP/IP-Ethernet. Numerous network services are available for communication, from the transparent virtual COM port to the Modbus/TCP gateway.

### Properties

#### Interfaces:

- **1 x RS232/422/485 selectable**
- **1 x Ethernet 10/100BaseT**
  - Autosensing/Auto-MDIX
- **alternate hardware configuration**
  - 20mA/TTY version see [Com-Server 20mA](#)

#### Management and connectivity:

- **Remote configuration**
  - Startup using WuTility (three clicks and you're done), DHCP, serial
  - Web-Based-Management via HTTP and HTTPS/TLS incl. certificate management
  - Telnet
  - Control sockets from your own applications
- **Transparent communication**
  - Windows COM Port Redirector and virtual COM ports with optional TLS-PSK encryption
  - Box-to-Box, optional TLS encrypted
  - TCP server sockets from your own applications, optionally TLS-PSK encrypted
  - OPC server
- **Expanded protocol support**
  - Modbus/TCP-Gateway for integrating serial Modbus/RTU slaves
  - FTP client / server
  - Telnet client / server
  - UDP Peer
  - SLIP
  - Wake-on-LAN

#### Power supply:

- **External**
  - Screw terminals, 12V-48V DC
- **Power-over-Ethernet (PoE)**
  - Phantom power using data pairs
  - Power over unused wire pairs

#### Standards & more

- **Conforms to standards both in office and industrial environments:**
  - High noise resistance per EN 61000-6-2
  - Low noise emission per EN 55032:2015 + A1 Cl. B, EN 61000-3-2 & EN 61000-3-3

- 5 year guarantee



Wish for something!

[Your suggestions for improvement and additions](#)

---

## Run modes

### [Windows COM Port Redirector](#)

Install the COM Port Redirector and configure your serial program on one of the virtual COM ports - done! Regardless of whether as a replacement for missing hardware COM ports, a solution for virtual environments such as VMware, HyperV, etc. or as a simple line driver, your serial communication becomes network capable without a single line of programming and, if desired, TLS-PSK encrypted. Multipoint mode and packeting options are of course also available.

[Data sheet with download link](#)

### [Box-to-Box](#)

In just a few clicks you can link 2 Com-Servers to each other logically and use an operating-system neutral, transparent and if desired TLS encrypted data tunnel through the network. Serial data are sent bi-directional and as fast as possible to the respective counterpart. Automatic reconnect functions in case of connection faults/dropouts are available as are multipoint operation and packeting options for fine tuning when using serial protocols.

To [application example ...](#)

### [TCP/UDP socket communication](#)

Network programming is today part of the standard repertoire of all programmers. Integrate your serial device easily into your own network application. Take connection control into your own hands as a TCP client, be contacted event-driven as a TCP server (optional with TLS-PSK encryption) or use the efficient, connectionless UDP protocol. Of course new multipoint operation and packeting options are also available here.

To [application example ...](#)

### [NEW! Modbus/TCP-Gateway](#)

Many devices such as energy meters, measuring transducers, frequency converters etc. have an RS232/422/485 interface and communicate via the Modbus/RTU protocol. The Com-Server integrates these devices quickly and reliably in Modbus/TCP environments.

### [FTP client/server](#)

Send and archive your serial data with the FTP standard tools on most operating systems. Serial outputs from scales, barcode readers etc. or status and error messages for example from UPSs are classic applications for the use of Com-Servers as FTP server or FTP client.

To [application example ...](#)

### [Multipoint mode](#)

Distribute the send data from your serial device to as many as six network stations at a time. Regardless of whether you want to archive or monitor, copies of the serial data can be retrieved on a configurable slave port. Filters for the authorized IP addresses are provided to protect against unauthorized access.

### [Packaging options](#)

Received serial protocols are often sensitive to pauses in the serial data flow. To prevent such timeouts and ensure complete transmission of the datagrams in a network packet, the Com-Server++ features numerous configuration options for detecting datagram limits (Start/Stop terminators, Start + Length, etc.).

---

## Technical data

### [Connections and displays:](#)

Serial port:	1x RS232-, RS422-, RS485 port, selectable DB9 connector plug 50 to 230.400 baud 7,8 data bits 1,2 stop bits Parity No, Even, Odd, Mark, Space Flow control No, RTS/CTS, Xon/Xoff
Serial modes:	RS232 RS422 4-wire bus master RS485 4-wire bus master RS485 4 wire with automatic control RS485 2 wire with automatic control

Network:	10/100BaseT Autosensing/Auto-MDIX RJ45 IPv6 on request
Galvanic isolation:	Network connection min. 1500 V
Supply voltage:	Power-over-Ethernet (PoE) or DC 12V .. 48V (+/-10%) or AC 18Veff .. 30Veff (+/-10%)
Supply connection:	Plug-in screw terminal, 5.08mm spacing Labeled "L+" and "M"
Current consumption:	PoE Class 1 (0.44 - 3.84W) or for external supply: typ. 55mA @24V DC max. 70mA @24VDC
Displays:	1 LED Power 1 LED Status 1 LED Error 2 LEDs Network Status




#### Housing and other data:

Housing:	Plastic compact housing for top-hat rail mount 105x22x75mm (LxWxH)
Enclosure rating:	IP20
Weight:	approx. 105g
Ambient temperature:	Storage: -40..+70°C Operating 0..+60°C (70°C on request)
Permissible relative humidity:	5..95% RH, non-condensing
MTBF:	637,767 h @25°C per MIL-HDBK-217
Life expectancy:	> 25 years at 25°C ambient temperature
Scope of delivery:	1x Com-Server ++ 1x Quick Guide


## Accessories

\*Net unit price for  
commercial users

### Power supplies

Plug-in power supply, 24V / 500mA DC with Euro plug	11021	21.00€	
Plug-in Power Supply, 24V / 750mA DC with Euro, US and UK plug	11026	38.00€	
Power supply for DIN rail, 24V / 630mA DC (merchandise, 2-year manufacturer's guarantee)	11080	33.00€	

### Mechanical Accessories

Mounting bracket for wall mounting	58812	11.20€	
19" DIN rail	58813	21.00€	
Wall mount housing, enclosure rating IP66 / IP67	11120	54.00€	

### Software

WuTility	00104	free	
Windows COM Port Redirector Legacy	00102	free	
Windows COM Port Redirector Win 95/98/Me	00101	free	
OPC Server	00103	free	

\* Our offering is intended only for commercial users. We will be happy to refer private end customers to trading partners through whom our products can be purchased.



We are available to you in person:

Wiesemann & Theis GmbH  
Porschestra. 12  
42279 Wuppertal  
Phone: +49 202/2680-110 (Mon.-Fri. 8 a.m. to 5 p.m.)  
Fax: +49 202/2680-265  
info@wut.de

© Wiesemann & Theis GmbH, subject to mistakes and changes: Since we can make mistakes, none of our statements should be applied without verification. Please let us know of any errors or misunderstandings you find so that we can become aware of and eliminate them.

[Data Privacy](#)