

Product overview:

230V coupling relay for Web-IO Digital

Article no.	Description	Design
57015	Coupling relay 1x changeover 230V	
	Contacts	
	Number of contacts: 1 changeover	D .
	Max. switching power AC1: 4000VA	
	Rated voltage: 250V	
	Max. switching voltage: 400V	
		II Chan I
	Coil	1111000
	Rated voltage: 24V DC	Will Street or S
	Rated power: 0.5W	II .
	Detailed technical data sheet and wiring examples	
57016	Coupling relay 2x changeover 230V	
	Contacts	
	Number of contacts: 2 changeover	0
	Max. switching power AC1: 2000VA	
	Rated voltage: 250V	7 2001
	Max. switching voltage: 400V	100
		II Chan I
	Coil	111000
	Rated voltage: 24V DC	Marie
	Rated power: 0.5W	П
	Detailed technical data sheet and wiring examples	

Article list

*Net unit price for commercial users

230V coupling relay - 1 x changeover

for DIN rail mount

57015 22.00€ 늘

230V coupling relay - 2 x changeover

57016 22.00€ 늘

for DIN rail mount

* Our offering is intended only for commercial users. We will be happy to refer private end customers to trading partners through whom our products can be purchased.



We are available to you in person:

Wiesemann & Theis GmbH

Porschestr. 12 42279 Wuppertal

Phone: +49 202/2680-110 (Mon.-Fri. 8 a.m. to 5 p.m.)

Fax: +49 202/2680-265

info@wut.de

© Wiesemann & Theis GmbH, subject to mistakes and changes: Since we can make mistakes, none of our statements should be applied without verification. Please let us know of any errors or misunderstandings you find so that we can become aware of and eliminate them.

Data Privacy